



IZIFIX POST

The product

IZIFIX post is a galvanised and plastic-coated profiled post that requires no installation accessories. It's compatible with BETAFENCE 3D ESSENTIAL and 3D+ and 6/5/6 and 8/6/8 double wire panels.

Once the fence panel is assembled with IZIFIX post, the structure cannot be dismantled, thanks to a retaining tab that folds into the post profile, securing the system and offering a reliable and secure fence.



Characteristics

Grey 7016 ● Green 6005 ●

POST LENGTH (mm)	POST CENTER DISTANCE (m)	FENCE HEIGHT - installa- tion on base plate - (mm)	FENCE HEIGHT - Sealed installation - (mm)
1075	2,54	1030	630
1275		1230	830
1475		-	1030
1575		1530	-
1775		1730	1230
1975		1930	1530
2075		2030	-
2175		-	1730
2475		2430	1930
2575		-	2030

- No accessories needed to assemble the panel and the post
- Compatible with all types of fence panels
- Angles from 60° to 180° can be easily achieved with a single post
- 75x50 mm post section
- Notch every 100 mm
- I/V : 5,38 m³
- A plastic cap closes the profile at the top and prevents water from seeping into the post.
- Galvanisation inside and out with polyester finish (minimum 60 micro-meters)