

LUX POST

The product

LUX 50-1,3 mm/e.m. or LUX 80-1,5/e.m. post with a longitudinal rack for attaching the accessories and clips required to tighten the wires and mesh.


Characteristics

Sendzimir ● Green6005 ● Grey 7016 ● Black 9005 ● White 9016 ○

- Carbon steel sheet in accordance with standard EN-10142. Tensile strength from 300 to 500 N/mm.
- Accessories secured to the rack with fixing screws. Weather-resistant polypropylene cap with UV protection.
- Reinforced galvanised wire clip, fixed lengthwise to the rack to prevent it from slipping.
- Sendzimir and plastic-coated finish with an anti-corrosion coating system.
- Minimal thickness : 100 micrometers



Chain link fence on Lux post



Knotted wire mesh on Lux post

FENCE HEIGHT (m)	START / TENSION POST			INTERMEDIATE POST		RANGES OF TENSION WIRE
	Post type	Nb. supports	Nb. staples	Post type	Nb. staples	
1,00	LUX 50 1,3 mm / e.m.	3	12	LUX 50 1,3 mm / e.m.	4	2
1,50	LUX 50 1,3 mm / e.m.	4	18	LUX 50 1,3 mm / e.m.	5	3
2,00	LUX 50 1,3 mm / e.m.	4	24	LUX 50 1,3 mm / e.m.	5	3
2,50	LUX 50 1,3 mm / e.m.	5	36	LUX 50 1,3 mm / e.m.	7	4
	LUX 80 1,5 mm / e.m.	5	36	LUX 80 1,5 mm / e.m.	7	4
3,00	LUX 80 1,5 mm / e.m.	5	36	LUX 80 1,5 mm / e.m.	7	4
4,00	LUX 80 1,5 mm / e.m.	6	48	LUX 80 1,5 mm / e.m.	9	5

WIRE MESH