

CONCRETE POST



The product

This concrete post is designed for installing wire mesh supplied in rolls.

Sturdy and durable, it offers excellent resistance to the elements and mechanical stress. Cost-effective and environmentally friendly, it's made from natural materials. The built-in holes allow tension wires to pass through easily, ensuring simple and reliable installation.

Characteristics

Concrete grey ●

- Material : ready-to-remove reinforced concrete
- Section : 10 x 10 cm
- Length : 200, 225 or 250 cm
- Diamond-pointed head
- Compatible with all types of flexible wire mesh sold in rolls
- Holes drilled along the height for inserting pins and tension wires
- Distance between 2 posts : around 2 m
- Corner and end posts must be reinforced with brace arms, notches are included to simplify their positioning

REF.	FINISH	HEIGHT (cm)	SECTION (cm)	WEIGHT (kg)	PALETTISATION
29215	Without notches	200	10 x 10	47	35 U
292161	With notches				30 U
88889*	Without notches	225		53	35 U
292162*	With notches				30 U
29216	Without notches	250		59	35 U
292163*	With notches				30 U



Post without notches



Post with notches



Brace arm

Brace arm

REF.	HEIGHT (cm)	SECTION (cm)	WEIGHT (kg)	PALETTISATION
29218	200	8 x 8	35	21 U
88889*	250		38	21 U

Pins ref. 29213*

- Sold in boxes of 100 units, which cannot be repackaged (weight: 2.3 kg)
- Dimension : 0,35 x 15 cm
- Material : raw steel in accordance with NF EN 16120 - galvanised coating in accordance with NF EN 10244-2

*Upon request

