

ALMADA LIGHT 100 CANTILEVER GATE

The product

ALMADA range of cantilever gates from Sbfm is ideal for fencing off residential areas; whether individual or collective, and public spaces like administrative offices and shops.

With a clear opening of 3 to 10 meters depending on the model chosen, this reliable product features an ingenious balancing system that ensures perfect and consistent performance.

A low-maintenance closure solution that requires no on-site intervention and can be adapted to all types of fields, including slopes and areas that are difficult to access.

Its plastic coating, which complies with current European standards, gives it excellent corrosion resistance. It has CE marking.



Characteristics

Grey 7016 ● Green 6005 ● Black 9005 ● White 9010 ○ Blue 5003 ● Red 3004 ●

- Ø 22 or 25 mm round bars depending on model
- 110 mm spacing between bars, preventing any passage through
- Sendzimir Z275 steel, powder coated (minimum 80 micrometers)
- Manual or motorised
- Non-intensive use gate
- 1 guide post
- 1 landing post
- CE marking

LENGTH	3 m	4 m	5 m	6 m
Guide (mm)	Post : 100 x 100 x 2 on base plate			
Landing (mm)	Post : 100 x 100 x 2 on base plate			
Frame (mm)	50 x 50 x 1,5			
Bars (mm)	Ø 22 round tube			
Beam (mm)	100 x 50 x 2			
C rail	3,5 mm thickness (60 x 70 mm)			
Lock	Locinox			
Tail	Non-barred with 1 tensioner			

Accessories



Locinox lock



Locinox strike plate



Cantilever guide

ALMADA 120 CANTILEVER GATE

The product

ALMADA range of cantilever gates from Sbfm is ideal for fencing off residential areas; whether individual or collective, and public spaces like administrative offices and shops.

With a clear opening of 3 to 10 meters depending on the model chosen, this reliable product features an ingenious balancing system that ensures perfect and consistent performance.

A low-maintenance closure solution that requires no on-site intervention and can be adapted to all types of fields, including slopes and areas that are difficult to access.

Its plastic coating, which complies with current European standards, gives it excellent corrosion resistance. It has CE marking.



Characteristics

Grey 7016 ● Green 6005 ● Black 9005 ● White 9010 ○ Blue 5003 ● Red 3004 ●

- Ø 22 or 25 mm round bars depending on model
- 110 mm spacing between bars, preventing any passage through
- Sendzimir Z275 steel, powder coated (minimum 80 micrometers)
- Manual or motorised
- Non-intensive use gate
- 1 guide post
- 1 landing post
- CE marking

LENGTH	3 m	4 m	5 m	6 m	7 m	8 m
Guide (mm)	*Post : 100 x 100 x 2 on base plate					
Landing (mm)	Post : 100 x 100 x 2 on base plate					
Frame (mm)	50 x 50 x 1,5				60 x 60 x 2	
Bars (mm)	Ø 22 round tube					
Beam (mm)	120 x 60 x 2				120 x 60 x 3	
C rail	3,5 mm thickness (60 x 70 mm)					
Lock	Locinox					
Tail	Non-barred with 1 tensioner					

*2200 and 2500 heights : guide frame made of 100 x 100 x 2 tube on screw-on base plate

Accessories



Locinox lock



Locinox strike plate



Cantilever guide plate

ALMADA + 160 CANTILEVER GATE

The product

ALMADA range of cantilever gates from Sbfm is ideal for fencing off residential areas; whether individual or collective, and public spaces like administrative offices and shops.

With a clear opening of 3 to 10 meters depending on the model chosen, this reliable product features an ingenious balancing system that ensures perfect and consistent performance.

A low-maintenance closure solution that requires no on-site intervention and can be adapted to all types of fields, including slopes and areas that are difficult to access.

Its plastic coating, which complies with current European standards, gives it excellent corrosion resistance. It has CE marking.



Characteristics

Grey 7016 ● Green 6005 ● Black 9005 ● White 9010 ○ Blue 5003 ● Red 3004 ●

- Ø 22 or 25 mm round bars depending on model
- 110 mm spacing between bars, preventing any passage through
- Sendzimir Z275 steel, powder coated (minimum 80 micrometers)
- Manual or motorised
- Non-intensive use gate
- 1 guide post
- 1 landing post
- CE marking

LENGTH	7 m	8 m	9 m	10 m
Guide (mm)	*Post : 100 x 100 x 2 on base plate			
Landing (mm)	Post : 100 x 100 x 2 on base plate			
Frame (mm)	80 x 80 x 2		80 x 80 x 3	
Bars (mm)	Ø 25 round tube			
Beam (mm)	160 x 80 x 3			
C rail	5 mm thickness (110 x 97 mm)			
Lock	Locinox			
Tail	Non-barred with 1 tensioner			

*2200 and 2500 heights : guide frame made of 100 x 100 x 2 tube on screw-on base plate

Accessories



Locinox lock



Locinox strike plate



Cantilever guide plate